

CAL FLUID MIL PRF 7024E TY II  
85969

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	CAL FLUID MIL PRF 7024E TY II
Product code	85969
Product Use Description	No data

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: liquid,, colourless

WARNING! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF INHALED OR SWALLOWED. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

**Potential Health Effects**

**Routes of exposure**

Inhalation, Skin contact

**Eye contact**

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

**Skin contact**

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

CAL FLUID MIL PRF 7024E TY II  
85969

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, Skin, lung (for example, asthma-like conditions)

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, and death

**Target Organs**

No data

**Carcinogenicity**

No data

**Reproductive hazard**

No data

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Components</b>	<b>CAS-No.</b>	<b>Concentration</b>
MINERAL SPIRITS ODORLESS (BASE DATA)	8052-41-3	<=100%

**4. FIRST AID MEASURES**

**Eyes**

CAL FLUID MIL PRF 7024E TY II  
85969

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

### **Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

### **Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### **Inhalation**

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

### **Notes to physician**

**Hazards:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

**Treatment:** No information available.

## **5. FIRE-FIGHTING MEASURES**

### **Suitable extinguishing media**

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Foam

### **Hazardous combustion products**

May form: carbon dioxide and carbon monoxide, hydrocarbons

### **Precautions for fire-fighting**

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

CAL FLUID MIL PRF 7024E TY II  
85969

**Flammability Class for Flammable Liquids**  
Combustible Liquid Class II

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions**

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

**Environmental precautions**

No data

**Methods for cleaning up**

No data

**7. HANDLING AND STORAGE**

**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

**Storage**

No data

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

CAL FLUID MIL PRF 7024E TY II  
85969**MINERAL SPIRITS ODORLESS**                      **8052-41-3**  
**(BASE DATA)**

---

ACGIH	time weighted average	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	2,900 mg/m3
OSHA Z1A	time weighted average	100 ppm
OSHA Z1A	time weighted average	525 mg/m3
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	100 ppm
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	525 mg/m3

**General advice**

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Exposure controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

**Eye protection**

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin and body protection**

Wear resistant gloves (consult your safety equipment supplier).  
To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory protection**

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

CAL FLUID MIL PRF 7024E TY II  
85969

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	liquid
<b>Form</b>	No data
<b>Colour</b>	colourless, clear
<b>Odour</b>	hydrocarbon-like
<b>Boiling point/boilingrange</b>	171.00 - 204.40 °C / 340 - 399.9 °F
<b>pH</b>	No data
<b>Flash point</b>	133 °F / 56 °C, Tag closed cup
<b>Evaporation rate</b>	0.11 (N-Butyl Acetate)
<b>Explosion limits</b>	0.7 %(V) 5.0 %(V)
<b>Vapour pressure</b>	0.52 mmHg @ 68.00 °F / 20.00 °C
<b>Vapour density</b>	4.9 (AIR=1)
<b>Density</b>	0.758 g/cm <sup>3</sup> @ 60.1 °F / 15.6 °C 6.42 lb/gal @ 60.00 °F / 15.56 °C
<b>Solubility</b>	No data
<b>Partition coefficient: n-octanol/water</b>	No data
<b>Autoignition temperature</b>	575 °F / 302 °C

## 10. STABILITY AND REACTIVITY

### Stability

Stable.

### Conditions to avoid

Avoid contact with:

### Incompatible products

Avoid contact with:, strong oxidizing agents

### Hazardous decomposition products

May form:, carbon dioxide and carbon monoxide, hydrocarbons

### Hazardous reactions

Product will not undergo hazardous polymerization.

### Thermal decomposition

CAL FLUID MIL PRF 7024E TY II  
85969

No data

## 11. TOXICOLOGICAL INFORMATION

### Acute oral toxicity

MINERAL SPIRITS ODORLESS      LD 50 Rat: > 5 g/kg  
(BASE DATA)

### Acute inhalation toxicity

### Acute dermal toxicity

MINERAL SPIRITS ODORLESS      LD 50 Rabbit: > 3 g/kg  
(BASE DATA)

## 12. ECOLOGICAL INFORMATION

### Aquatic toxicity

#### Acute and Prolonged Toxicity to Fish

No data

#### Acute Toxicity to Aquatic Invertebrates

No data

### Environmental fate and pathways

No data

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

## 14. TRANSPORT INFORMATION

CAL FLUID MIL PRF 7024E TY II  
85969

**IMDG:**

UN1268, PETROLEUM DISTILLATES, N.O.S. (ALIPHATIC HYDROCARBONS, )  
3, III

**IATA\_P:**

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC HYDROCARBONS, ) 3, III

**IATA\_C:**

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC HYDROCARBONS, ) 3, III

**CFR\_ROAD:**

UN1268, Petroleum distillates, n.o.s. 3, III

**CFR\_RAIL:**

UN1268, Petroleum distillates, n.o.s. 3, III

**CFR\_INWTR:**

UN1268, Petroleum distillates, n.o.s. 3, III

Dangerous goods descriptions (if indicated above) may not reflect package size, quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**15. REGULATORY INFORMATION**

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

**SARA 313 Component(s)**

	<b>Health</b>	<b>Flammability</b>	<b>Reactivity</b>	<b>Other</b>
<b>HMIS</b>	1*	2	0	
<b>NFPA</b>	1	2	0	

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This

**ASHLAND**  
**SAFETY DATA SHEET**

CAL FLUID MIL PRF 7024E TY II  
85969

Page: 9  
Revision Date: 01/24/2008  
Print Date: 1/23/2009  
MSDS Number: R0267239  
Version: 1.7

MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).