

PRO CITRUS PREP 1/5 GA

 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PRO CITRUS PREP 1/5 GA

General or Generic ID: PREMIUM AUTOMOTIVE DETAIL PRODUCT

Company

The Valvoline Company
 P.O. Box 14000
 Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263
 Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
SURFACTANTS		1.0- 31.0
SODIUM METASILICATE PENTAHYDRATE	6834-92-0	1.0- 31.0
GLYCOL ETHER		1.0- 31.0
TRISODIUM PHOSPHATE ANHYDROUS	7601-54-9	1.0- 31.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Material is corrosive to eyes. May cause burns.

Skin

Can cause skin burns and other permanent skin damage. Passage through the skin may add to toxic effects from breathing or swallowing.

Swallowing

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation, burns and tissue damage. Shock may occur. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful or fatal. May cause severe irritation and burns to the nose, throat, and respiratory tract. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may

include: metallic taste, mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, shortness of breath, difficult breathing, kidney damage, liver damage, lung damage.

Target Organ Effects

Studies with rabbits indicate that sustained, occluded skin contact with undiluted surfactant may result in the development of inflammatory changes in the lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: kidney damage, liver damage.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

There is no information available. The chance of this material causing cancer is unknown. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes.

Swallowing

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin

artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions).

5. FIRE FIGHTING MEASURES

Flash Point

> 200.0 F (93.3 C) ESTIMATED

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 3, Flammability - 1, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious clothing and boots. To prevent skin contact, wear impervious full-body protective clothing.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

SURFACTANTS

No exposure limits established

SODIUM METASILICATE PENTAHYDRATE (6834-92-0)

No exposure limits established

GLYCOL ETHER

No exposure limits established

TRISODIUM PHOSPHATE ANHYDROUS (7601-54-9)

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
No data

Vapor Pressure
No data

Specific Vapor Density
No data

Specific Gravity
1.042 @ 70.00 F

Liquid Density
8.680 lbs/gal @ 70.00 F
1.042 kg/l @ 21.00 C

Percent Volatiles (Including Water)
No data

Evaporation Rate
No data

Appearance
CLEAR

State
LIQUID

Physical Form
No data

Color
YELLOW

Odor
CITRUS

pH
12.9 - 13.3

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability
Stable.

Incompatibility

Avoid contact with: strong acids, strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.,8,UN3266,II

Container/Mode:

DRUMS/SURFACE - NO EXCEPTIONS

NOS Component:

SODIUM METASILICATE PENTAHYDRATE

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

Component

Component

TRISODIUM PHOSPHATE

5000

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire() Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information
SODIUM PHOSPHATE, TRIBASIC

7601-54-9

Pennsylvania RTK Label Information
PHOSPHORIC ACID, TRISODIUM SALT

7601-54-9

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page