

The Valvoline Company

Date Prepared: 03/10/03

PRO MAXXGLOSS 1/55 GA

MSDS No: 510.0362533-001.002I

---

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PRO MAXXGLOSS 1/55 GA

General or Generic ID: PREMIUM AUTOMOTIVE DETAIL PRODUCT

Company

The Valvoline Company  
P.O. Box 14000  
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263  
Information: 1-859-357-7206

---

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
GLYCERINE	56-81-5	1.0- 30.0

---

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

May cause mild skin irritation. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects.

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways).

Target Organ Effects

No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

#### Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

#### Other Health Effects

No data

#### Primary Route(s) of Entry

No data

---

#### 4. FIRST AID MEASURES

##### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

##### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

##### Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

##### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

#### Note to Physicians

No data

---

#### 5. FIRE FIGHTING MEASURES

##### Flash Point

> 200.0 F (93.3 C) ESTIMATED

##### Explosive Limit

No data

##### Autoignition Temperature

No data

##### Hazardous Products of Combustion

May form: acrolein, carbon dioxide and carbon monoxide, formaldehyde, silicates, various hydrocarbons.

#### Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. No special fire hazards are known to be associated with this product.

#### Extinguishing Media

regular foam, carbon dioxide, dry chemical.

#### Fire Fighting Instructions

Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

#### NFPA Rating

Health - 1, Flammability - 0, Reactivity - 0

---

### 6. ACCIDENTAL RELEASE MEASURES

#### Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

#### Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

---

### 7. HANDLING AND STORAGE

#### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

#### Storage

Do not store near extreme heat, open flame, or sources of ignition.

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

#### Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

#### Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

#### Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

#### Exposure Guidelines

##### Component

-----

GLYCERINE (56-81-5)

OSHA VPEL 5.000 mg/m3 - TWA respirable fraction

OSHA VPEL 10.000 mg/m3 - TWA total dust

ACGIH TLV 10.000 mg/m3 - TWA

---

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

##### Boiling Point

(for component) 340.0 F (171.1 C)

##### Vapor Pressure

(for component) 3.000 mmHg

##### Specific Vapor Density

No data

##### Specific Gravity

.980 @ 70.00 F

##### Liquid Density

No data

##### Percent Volatiles (Including Water)

No data

##### Evaporation Rate

No data

##### Appearance

No data

##### State

LIQUID

##### Physical Form

EMULSION

##### Color

WHITE

##### Odor

PINA COLADA

pH 8.5 - 8.7

Viscosity 1825.0 - 1900.0 cps @ SPINDLE #4 @ 70°F

---

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: acrolein, carbon dioxide and carbon monoxide, formaldehyde, silicates, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

---

11. TOXICOLOGICAL INFORMATION

No data

---

12. ECOLOGICAL INFORMATION

No data

---

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

---

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:  
Not Regulated

Container/Mode:  
CASES/SURFACE - NO EXCEPTIONS

NOS Component:  
None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

---

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed( ) Fire( ) Reactive( ) Sudden  
Release of Pressure( )

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

Pennsylvania RTK Label Information

1,2,3-PROPANETRIOL

56-81-5

---

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page