

MATERIAL SAFETY DATA SHEET

GUMOUT® XL FUEL INJECTOR CLEANER

1. PRODUCT AND COMPANY IDENTIFICATION

MSDS Number: 25125

Version Date: 4/8/2004

Product Name: GUMOUT® XL FUEL INJECTOR CLEANER

Product Use: Fuel injector cleaner

Synonyms: GUMOUT XL POWERWING, 5038694, 5037722, 161104

Company Information

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4427
USA

Phone Numbers

Medical Emergency: 1-800-546-6040
Transportation Emergency (USA): 1-800-424-9300
Transportation Emergency (International):
1-703-527-3887(Call Collect)
MSDS Assistance: 1-800-546-6227
Fax On Demand: 1-800-546-6227
Technical Assistance: 1-800-458-4998
Customer Service: 1-800-468-8397
Fax Number: 713-217-3181
Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
KEROSENE	8008-20-6	90 - 95	Yes
DETERGENT/DISPERSANT	MIXTURE	< 10	No
STABILIZER	TRADESECRET	< 1	No

This product meets the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Hazards:

Flammable/Combustible X **Acute Toxin** X **Chronic Toxin** -- **Carcinogen** --
Pressure -- **Reactive** -- **Exposure Limit** -- **Target Organ** -- **Other** --

Other: No information available

3. HAZARDS IDENTIFICATION

Emergency and Hazards Overview

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

NFPA Ratings: Health 1 Flammability 2 Reactivity 0

Primary Route of Exposure: Skin X Inhalation X Eye --

Health Effect Information

Eye Contact: Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact. Based on testing of similar products and/or components. Exposure to high concentrations of vapors may be irritating to the eyes.

Skin Contact: Avoid skin contact. This product may cause slight skin irritation upon direct contact. Based on testing of similar products and/or components. Prolonged or repeated skin contact may result in dryness, chapping, and reddening. May be absorbed through skin.

MATERIAL SAFETY DATA SHEET

MSDS Number: 25125

GUMOUT® XL FUEL INJECTOR CLEANER

Page 2 of 8

Inhalation: This product is not expected to pose an inhalation hazard under conditions of foreseeable use. Avoid prolonged inhalation of vapors. This product may be considered a low health hazard unless inhaled in very high concentrations. Acute and chronic exposure to vapors may be irritating to the respiratory tract. Severe intoxication may lead to drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Intentional misuse by deliberately concentrating and inhaling this product can be harmful or fatal.

Ingestion: Do not ingest. Ingestion is expected to be relatively non-toxic unless aspiration occurs. Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting with a further risk of aspiration. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

Other: No information available

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. Use a hand or skin lotion to prevent dryness.

Inhalation: If victim exhibits signs of vapor intoxication remove to fresh air. If discomfort persists seek medical attention.

Ingestion: Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. Seek immediate medical attention.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: 125 F, 51.7 C

Test Method: ASTM D-93 (P.M.C.C.)

Flammable Limits in Air

Upper Percent: 6%

Lower Percent: 1.1%

Autoignition Temperature: No data available

Test Method: No information available

NFPA Classification: Class II combustible liquid

Extinguishing Media: Use water spray (fog), dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: No special fire fighting procedures are required.

MATERIAL SAFETY DATA SHEET

MSDS Number: 25125

GUMOUT® XL FUEL INJECTOR CLEANER

Page 3 of 8

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: None

Other: No information available

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Remove all sources of ignition. Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Provide adequate ventilation during clean-up.

Regulatory Notifications: No notification required

Containment and Clean up: Do not allow spill to enter sewers or watercourses. Absorb with solvent absorbent material.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: All ignition sources in the area should be controlled. Do not open or use in unventilated, enclosed or confined spaces.

Storage: Do not transfer to unmarked containers. Store in a cool, well ventilated area in closed containers away from heat, sparks, open flame or oxidizing materials.

Empty Container Warnings

Drums: Not applicable

Plastic: Empty container may retain product residues. Do not reuse this container.

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

This product does not contain any components with OSHA or ACGIH exposure limits.

Personal Protective Equipment

Eye/Face Protection: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

Skin Protection: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. Launder soiled clothes.

Respiratory Protection: Respiratory protection is not required under conditions of normal use. If excessive levels of mists or vapors are generated while using this product, use an organic vapor respirator. All respirators must be NIOSH certified. See Section 3, Health Effect Information, Inhalation.

Personal Hygiene: Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

MATERIAL SAFETY DATA SHEET

MSDS Number: 25125

GUMOUT® XL FUEL INJECTOR CLEANER

Page 4 of 8

Engineering Controls / Work Practices

Ventilation: General room ventilation is normally sufficient to prevent buildup of hazardous concentrations. If product is used in enclosed or confined spaces, adequate ventilation must be provided to prevent buildup of vapors or mists.

Other: The OSHA PEL and ACGIH TLV for stoddard solvent is 525 mg/m³. NIOSH recommended limits for petroleum distillates are 350 mg/m³ (10-hr TWA) and 1800 mg/m³ (15-min ceiling).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pale yellow	
Odor: Solvent	Vapor Pressure: 2 mm Hg @ 68 F
Physical state: Liquid	Vapor Density (air=1): 4.9
pH: No data available	Percent Volatile by Volume: > 70 %
Boiling Point: 340 - 400 F, 171.1 - 204.4 C	Volatile Organic Content: No data available
Melting Point: No data available	Molecular Weight: No data available
Specific Gravity: 0.82	Average Carbon Number: No data available
Pour Point: No data available	Viscosity @ 100 F: No data available
	Viscosity @ 40 C: No data available
Solubility in Water: Insoluble in water, soluble in hydrocarbons	
Octanol / Water Coefficient: Log K_{ow} = No data available	

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: Keep away from heat, sparks, open flames and other ignition sources.

Incompatible Materials to Avoid: May react with strong oxidizing agents.

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

MATERIAL SAFETY DATA SHEET

MSDS Number: 25125

GUMOUT® XL FUEL INJECTOR CLEANER

Page 5 of 8

Carcinogenicity: Light hydrocarbons such as stoddard solvent, VM & P naphtha and C10-C11 isoparaffins have produced kidney damage in male rats, but not in female rats or mice. The Environmental Protection Agency (EPA) has concluded that rat kidney damage and tumors induced by light petroleum hydrocarbons are not relevant to humans. Various naphthas tested were not carcinogenic in mouse skin painting studies conducted by the American Petroleum Institute (API). The International Agency for Research on Cancer (IARC) has concluded that petroleum solvents are Group 3 substances, "not classifiable as to their carcinogenicity to humans".

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: May be toxic to aquatic organisms.

Terrestrial Toxicity: No information available

Chemical Fate and Transport: This substance is expected to biodegrade at a moderate rate and be "inherently" biodegradable according to OECD guidelines.

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: Dispose of residual products and empty containers responsibly. Refer to state and local regulations for additional disposal requirements.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility. The discarded material should be recycled if possible.

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): Not Regulated

Highway / Rail (Non-Bulk): CONSUMER COMMODITY, ORM-D

For US shipments, US DOT law requires the shipper to determine the proper shipping description of the material that is being shipped. The shipping information and description contained in this section may not be suitable for all shipments of this material, but may help the shipper determine the proper shipping description for a particular shipment.

MATERIAL SAFETY DATA SHEET

MSDS Number: 25125

GUMOUT® XL FUEL INJECTOR CLEANER

Page 6 of 8

International Information

Vessel: IMDG Regulated: X IMDG Not Regulated: --
Air: ICAO Regulated: X ICAO Not Regulated: --

Other: No information available

15. Regulatory Information

Regulatory Lists Searched: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depleters, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCOMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US - TSCA Section (12)(b) - export notification

State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

Inventories: 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA, 85 - China Inventory

Regulatory Search Results:

KEROSENE: 17, 23, 50, 61, 63, 66, 67, 68, 69, 80, 81, 83, 84, 85

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313: Consumer products are not regulated under SARA, Title III, Section 313.

IARC: No information available

SARA 311 / 312 Categories

Acute: X Chronic: -- Fire: X Pressure: -- Reactive: --
Not Regulated: --

Canadian WHMIS Classification

Class B - Flammable and Combustible Material, Division 3, Combustible Liquid
Class D - Poisonous and infectious material, Division 2B, Toxic Material

European Union Classification

Hazard Symbols:

Harmful / Xn / X in square.

MATERIAL SAFETY DATA SHEET

MSDS Number: 25125

GUMOUT® XL FUEL INJECTOR CLEANER

Page 7 of 8

Risk Phrases:

R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

Safety Phrases:

S2: Keep out of the reach of Children.
S23: Do not breathe gas/fumes/vapour/spray.
S24: Avoid contact with skin.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

Front Label:

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

Read carefully other cautions on back.

Back Label:

DANGER: Contains petroleum distillates. Prolonged and repeated skin contact may cause drying of skin.

PRECAUTIONARY MEASURES: Keep away from heat and flames. Avoid breathing of mists and vapors. Use only in well ventilated areas. Keep container closed. Avoid skin and eye contact. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If inhaled, breathe fresh air. For contact with skin or eyes wash thoroughly with water.

KEEP OUT OF REACH OF CHILDREN.

MSDS Revisions

Previous Version Date: 6/27/2002

Previous Version Information

Section 5. Fire and Explosion Information

Section 14. Transportation Information

Other

No information available

Prepared By:

SOPUS Products

P.O. Box 4427

Houston, TX 77210-4427 USA

MATERIAL SAFETY DATA SHEET
GUMOUT® XL FUEL INJECTOR CLEANER

MSDS Number: 25125

Page 8 of 8

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, SOPUS Products must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information, the results to be obtained from the use thereof, or that any such use do not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.