



1. Chemical product and company identification

Product name	LUBECON SERIES 525
MSDS#	69546-AE
Code	69546-AE
Product use	Lubricant
Manufacturer	Castrol Industrial North America, Inc. 150 W. Warrenville Road Naperville, IL 60563
Supplier	Castrol Industrial North America, Inc. 150 W. Warrenville Road Naperville, IL 60563 Product Information: 1-800-621-2661
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)

2. Composition/information on ingredients

Ingredient name	CAS #	% by weight	Exposure limits
Distillates (petroleum), hydrotreated middle	64742-46-7	70 - 75	ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist STEL: 10 mg/m ³ 15 minute(s). Form: Mist OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist

3. Hazards identification

Physical state	Liquid.
Color	Amber.
Emergency overview	CAUTION! MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Do not ingest. Do not get in eyes, on skin or clothing. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Potential Health Effects	
Eyes	May cause eye irritation.
Skin	May cause skin irritation.
Inhalation	May cause respiratory tract irritation.
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhea.

Medical conditions aggravated by overexposure None identified.

[See toxicological Information \(section 11\)](#)

4. First aid measures

Eye Contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops.

Skin Contact Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if irritation develops.

Ingestion Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.

5. Fire-fighting measures

Flammability of the product May be combustible at high temperature.

Flash point 121 °C (Open cup) Cleveland.
118 °C (Closed cup) Pensky-Martens.

Products of combustion These products are carbon oxides (CO, CO₂).

Unusual fire/explosion hazards This material is not explosive as defined by established regulatory criteria.

This material is not explosive as defined by established regulatory criteria.

Fire fighting media and instructions In case of fire, use water fog, foam, dry chemicals, or carbon dioxide.

Protective clothing (fire) Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal Precautions Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").

Environmental precautions and clean-up methods If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Minimize contact of spilled material with soils to prevent runoff to surface waterways. See Section 13 for Waste Disposal Information.

Personal protection in case of a large spill Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

7. Handling and storage

Handling Do not ingest. Do not get in eyes, on skin or on clothing. Avoid contact with skin and clothing. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Use only with adequate ventilation. Wash thoroughly after handling.

Storage Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Product Name LUBECON SERIES 525	MSDS# 69546-AE	Page: 2/5
Version 1	Date of issue 02/10/2005.	Format US
	Build 4.1.1	Language ENGLISH (ENGLISH)

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Distillates (petroleum), hydrotreated middle

Occupational exposure limits

ACGIH (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Mist

STEL: 10 mg/m³ 15 minute(s). Form: Mist

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Mist

Control Measures

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Hygiene measures

Wash hands after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Personal protection

Eyes

Avoid contact with eyes. Safety glasses with side shields.

Skin and Body

Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

Wear suitable gloves.

Not available.



Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state

Liquid.

Odor

Petroleum

Color

Amber.

Density

840 kg/m³ (0.84 g/cm³) at 15.6°C

Solubility

Insoluble in cold water, hot water.

Viscosity

Kinematic: 22 mm²/s (22 cSt) at 40°C
22 cSt at 40C (typical)

10. Stability and reactivity

Stability and Reactivity

The product is stable.

Conditions to avoid

Not available.

Incompatibility with various substances

Reactive with oxidizing agents, acids, alkalis.

Hazardous Decomposition Products

Not available.

Hazardous polymerization

Will not occur.

Product Name LUBECON SERIES 525

MSDS#

69546-AE

Page: 3/5

Version 1

Date of issue 02/10/2005.

Format US

Language ENGLISH

Build 4.1.1

(ENGLISH)

11. Toxicological information

Chronic toxicity

Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

Mutagenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.

Reproductive effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.

Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

RCRA Waste Code(s)

USED OIL

Remarks

No additional remark.

Consult your local or regional authorities.

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal regulations

US INVENTORY (TSCA): In compliance.

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: LUBECON SERIES 525: Immediate (Acute) Health Hazard

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: This material is not regulated under CERCLA Sections 103 and 107.

State regulations

No products were found.

Product Name LUBECON SERIES 525

MSDS#

69546-AE

Page: 4/5

Version 1

Date of issue 02/10/2005.

Format US

Language ENGLISH

Build 4.1.1

(ENGLISH)

Inventories

AUSTRALIAN INVENTORY (AICS): Not listed.

CANADA INVENTORY (DSL): Not listed.

CHINA INVENTORY (IECS): Not listed.

EC INVENTORY (EINECS/ELINCS): Not listed.

JAPAN INVENTORY (ENCS): Not listed.

KOREA INVENTORY (ECL): Not listed.

PHILIPPINE INVENTORY (PICCS): Not listed.

16. Other information

Label Requirements

CAUTION!

MAY CAUSE EYE IRRITATION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :

Health 1
Flammability 1
Physical Hazard 0
Personal protection B

National Fire Protection Association (U.S.A.)



Other special considerations

PETROLEUM OIL: STEL = 10 mg/M3. Using terminology of the International Agency for Research on Cancer (IARC), the petroleum distillates listed in Section II are classified by the supplier as severely processed. Not all those listed in Section II may be present. The supplier has stated that these distillates do not require a carcinogen label as defined by OSHA 29 CFR 1910.1200. No component known to be present in this product at >0.1% is presently listed as a carcinogen by IARC, NTP or OSHA.

History

Date of issue

02/10/2005.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product Name LUBECON SERIES 525

MSDS#

69546-AE

Page: 5/5

Version 1

Date of issue 02/10/2005.

Format US

Language ENGLISH

Build 4.1.1

(ENGLISH)