

# Material Safety Data Sheet

COMPRO\* XL-R COMPRESSOR FLUID



## 1 . Product and company identification

<b>Common name</b>	: COMPRO* XL-R COMPRESSOR FLUID
<b>Code</b>	: 490-224, CPXR
<b>Material uses</b>	: This product is used for the lubrication of air and inert gas compressors of the reciprocating type. This compressor oil should NEVER be used in equipment compressing pure oxygen.
<b>Manufacturer</b>	: PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3
<b><u>In case of emergency</u></b>	: <b>Petro-Canada: 403-296-3000</b> <b>Canutec Transportation:</b> <b>613-996-6666</b> <b>Poison Control Centre: Consult local telephone directory for emergency number(s).</b>

## 2 . Hazards identification

<b>Odor</b>	: Mild petroleum oil like.
<b>OSHA/HCS status</b>	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.
<b>Emergency overview</b>	: No specific hazard.
<b>Routes of entry</b>	: Dermal contact. Eye contact. Inhalation. Ingestion.
<b><u>Potential acute health effects</u></b>	
<b>Eyes</b>	: Slightly irritating to the eyes.
<b>Skin</b>	: Slightly irritating to the skin.
<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Ingestion</b>	: No known significant effects or critical hazards.
<b>Medical conditions aggravated by over-exposure</b>	: Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation.
<b>See toxicological information (section 11)</b>	

## 3 . Composition/information on ingredients

<b><u>Name</u></b>	<b><u>CAS number</u></b>	<b><u>%</u></b>
Mixture of severely hydrotreated and hydrocracked base oil (petroleum).	Not available.	-

The base oil may be a mixture of the following CAS#s: 8042-47-5, 64742-46-7, 64742-52-5, 64742-54-7, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1, 178603-64-0, 178603-65-1, 178603-66-2, 445411-73-4

## 4 . First aid measures

<b>Eye contact</b>	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
<b>Skin contact</b>	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Get medical attention if irritation occurs. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.
<b>Inhalation</b>	: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
<b>Ingestion</b>	: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.
<b>Protection of first-aiders</b>	: No action shall be taken involving any personal risk or without suitable training.

## 5 . Fire-fighting measures

- Flammability of the product** : May be combustible at high temperature.
- Products of combustion** : Carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO<sub>x</sub>), sulphur oxides (SO<sub>x</sub>), phosphorus oxides (PO<sub>x</sub>), hydrocarbons, smoke and irritating vapours as products of incomplete combustion.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : No specific hazard.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Low fire hazard. This material must be heated before ignition will occur.
- Special remarks on explosion hazards** : Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

## 6 . Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

## 7 . Handling and storage

- Handling** : Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk. Evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, acids, alkalis.
- Storage** : Keep container tightly closed. Store away from incompatible materials (see section 10). Keep container in a cool, well-ventilated area.

## 8 . Exposure controls/personal protection

### Product name

Mixture of severely hydrotreated and hydrocracked base oil (petroleum).

### Exposure limits

**ACGIH TLV (United States). Notes: (oil mist)**

TWA: 5 mg/m<sup>3</sup> 8 hour/hours.

STEL: 10 mg/m<sup>3</sup> 15 minute/minutes.

**Consult local authorities for acceptable exposure limits.**

- Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control airborne levels. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protection

#### Eyes

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

#### Skin

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 8 . Exposure controls/personal protection

- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
Recommended: organic vapor filter
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Recommended: neoprene, nitrile, polyvinyl alcohol (PVA), Viton.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9 . Physical and chemical properties

- Physical state** : Viscous liquid.
- Flash point** : Open cup: 236°C (456.8°F) (Cleveland.).
- Auto-ignition temperature** : Fire Point:  
266°C (510.8°F)
- Flammable limits** : Not available.
- Color** : Pale yellow.
- Odor** : Mild petroleum oil like.
- pH** : Not applicable.
- Boiling/condensation point** : Not available.
- Pour point** : -18°C (0°F)
- Melting/freezing point** : Not available.
- Relative density** : 0.8969 kg/L @ 15°C (59°F)
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Volatility** : Non-volatile.
- Odor threshold** : Not available.
- Evaporation rate** : Not available.
- Viscosity** : 67 cSt @ 40°C (104°F), 8.3 cSt @ 100°C (212°F), VI=91
- Solubility** : Insoluble in water.
- LogK<sub>ow</sub>** : Not available.
- Softening Point** : Not available.
- Dropping Point** : Not available.
- Penetration** : Not available.
- Physical/chemical properties comments** : Not available.

## 10 . Stability and reactivity

- Stability and reactivity** : The product is stable.
- Conditions of instability** : Not available.
- Incompatibility with various substances** : Reactive with oxidizing agents, acids and alkalis.
- Hazardous decomposition products** : May release CO<sub>x</sub>, NO<sub>x</sub>, SO<sub>x</sub>, PO<sub>x</sub>, diphenylamine, hydrocarbons, smoke and irritating vapours when heated to decomposition.
- Hazardous polymerization** : Will not occur.

## 11 . Toxicological information

### Toxicity data

<u>Product/ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Mixture of severely hydrotreated and hydrocracked base oil (petroleum).	LD50	>5000 mg/kg	Oral	Rat
	LD50	>2000 mg/kg	Dermal	Rabbit
	LC50	>2500 mg/m <sup>3</sup> (4 hour/hours)	Inhalation	Rat

### Specific effects

**Carcinogenic effects** : Not listed as carcinogen by OSHA, NTP or IARC.

**Mutagenic effects** : No known significant effects or critical hazards.

**Teratogenicity / Reproductive toxicity** : No known significant effects or critical hazards.

### Sensitization

**Ingestion** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Eyes** : Slightly irritating to the eyes.

**Skin** : Slightly irritating to the skin.

**Synergistic products** : Not available.

## 12 . Ecological information

### Ecotoxicity data

<u>Product/ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
--------------------------------	----------------	---------------	---------------

**Environmental precautions** : No known significant effects or critical hazards.

**Bioconcentration factor** : Not available.

**BOD and COD** : Not available.

**Biodegradable/OECD** : Not available.

**Mobility** : Not available.

**Special remarks on the products of biodegradation** : Not available.

## 13 . Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

## 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
<b>TDG Classification</b>	Not regulated.	-	-	-		-
<b>DOT Classification</b>	Not available.	Not available.	Not available.	-		-

PG\* : Packing group

## 15. Regulatory information

### United States

**HCS Classification** : Not regulated.

**U.S. Federal regulations** : Not available.

### Canada

**WHMIS (Canada)** : Not controlled under WHMIS (Canada).

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

### EU regulations

**Risk phrases** : This product is not classified according to EU legislation.

### International regulations

#### International lists

**CANADA INVENTORY (DSL)** : Listed

**EC INVENTORY (EINECS/ELINCS)** : Listed

**TSCA 8(b) inventory** : Listed

## 16. Other information

**Hazardous Material Information System (U.S.A.)** :

Health	1
Fire hazard	1
Reactivity	0
Personal protection	B

**National Fire Protection Association (U.S.A.)** :



### References

: Available upon request.  
\* Marque de commerce de Petro-Canada - Trademark

**Date of printing** :

**7/24/2006.**

**Date of issue** :

**7/24/2006.**

**Date of previous issue** :

**No previous validation.**

**Responsible name** :

**Product Safety - JDW**

**Version** :

**1**

**For Copy of (M)SDS** :

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax: 1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

## 16 . Other information

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.