

MATERIAL SAFETY DATA SHEET  
Revision Date: 10/27/2003

-----  
SECTION 1            PRODUCT AND COMPANY    IDENTIFICATION  
-----

PRODUCT:    SHELL™ DIESEL READY Coolant/AF Prediluted 50/50  
MSDS NUMBER: 400935E - 1  
PRODUCT CODE(S):        94069

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX.    77210-4453

TELEPHONE NUMBERS

Spill Information: (877) 242-7400  
Health Information: (877) 504-9351  
MSDS Assistance Number: (877) 276-7285

-----  
SECTION 2            PRODUCT/INGREDIENTS  
-----

CAS#	CONCENTRATION	INGREDIENTS
		Coolant/Antifreeze
107-21-1	45 - 54.99 %weight	Ethylene Glycol
7732-18-5	45 - 54.99 %weight	Deionized water
Mixture	1 - 2.99 %weight	Scale and corrosion additives

-----  
SECTION 3            HAZARDS IDENTIFICATION  
-----

EMERGENCY OVERVIEW

Appearance & Odor: Purple liquid. Odorless.  
Health Hazards: Toxic and harmful if inhaled. May be harmful or fatal if swallowed. Do not induce vomiting. May cause aspiration pneumonitis.  
NFPA Rating (Health, Fire, Reactivity): 2, 1, 0  
Hazard Rating: Least - 0        Slight - 1        Moderate - 2        High - 3  
Extreme - 4

Inhalation:  
Toxic and harmful if inhaled.

Eye Irritation:  
May cause slight irritation of the eyes. If irritation occurs, a temporary burning sensation, minor redness, swelling, and/or blurred vision may result.

Skin Contact:  
May cause slight irritation of the skin. If irritation occurs, a temporary burning sensation and minor redness and/or swelling may result. Other adverse effects not expected from brief skin contact.

Ingestion:  
Toxic and harmful if swallowed. Contains ethylene glycol and/or diethylene glycol which are toxic when swallowed. A lethal dose for an adult is 1 ml per kilogram or about 4 ounces (1/2 cup). Severe kidney damage can occur as a

result of ingestion. Liquid can directly enter the lungs (aspiration) when swallowed or vomited. Serious lung damage and possibly fatal chemical pneumonia (chemical pneumonitis) can develop if this occurs.

Other Health Effects:

Refer to Section 11, Toxicological Information, for specific information on the following effects:

Developmental Toxicity

Primary Target Organs:

The following organs and/or organ systems may be damaged by overexposure to this material and/or its components:

Kidney, Liver

Signs and Symptoms:

Irritation as noted above. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin); in severe cases death may occur. Kidney damage may be indicated by changes in urine output or appearance, pain upon urination or in the lower back or general edema (swelling from fluid retention). Liver damage may be indicated by loss of appetite, jaundice (yellowish skin and eye color), fatigue and sometimes pain and swelling in the upper right abdomen.

Aggravated Medical Conditions:

Pre-existing eye, skin, respiratory, liver and kidney disorders and may be aggravated by exposure to this product.

For additional health information, refer to section 11.

---

#### SECTION 4 FIRST AID MEASURES

---

Inhalation:

If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin:

Flush exposed area with water and follow by washing with soap if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye:

Flush eyes with plenty of water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision or swelling occur, transport to nearest medical facility for additional treatment.

Ingestion:

DO NOT take internally. DO NOT INDUCE VOMITING. If victim is alert, rinse mouth and drink 1/2 to 1 glass of water to help dilute the material and call a doctor or poison control center. DO NOT GIVE LIQUIDS TO A DROWSY, CONVULSING OR UNCONSCIOUS PERSON. Keep the victim calm. Transport to the nearest medical facility for additional treatment.

Note to Physician:

Ethylene Glycol (EG) and Diethylene Glycol (DEG) intoxication may initially produce behavioral changes, drowsiness, vomiting, diarrhea, thirst, and convulsions. EG and DEG are nephrotoxic. End stages of poisoning may include renal damage or failure with acidosis. Supportive measures, supplemented with hemodialysis if indicated, may limit the progression and severity of toxic effects. For ETHYLENE GLYCOL POISONING, intravenous ethanol is a recognized

antidotal treatment; other antidotal treatments also exist for ethylene glycol poisoning.

---

SECTION 5 FIRE FIGHTING MEASURES

---

Flash Point [Method]: 265 °F/129.44 °C [ Cleveland Open Cup]

Extinguishing Media:

Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions:

Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus.

---

SECTION 6 ACCIDENTAL RELEASE MEASURES

---

Protective Measures:

May burn although not readily ignitable.

Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

Spill Management:

Shut off source of leak if safe to do so. Dike and contain spill.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Reporting:

U.S. regulations require reporting releases of this material to the environment which exceed the reportable quantity to the National Response Center at (800)424-8802.

---

SECTION 7 HANDLING AND STORAGE

---

Precautionary Measures:

Do not take internally. Do not taste or swallow. Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Storage:

Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

## Container Warnings:

Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

---

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

---

Ethylene Glycol ACGIH TLV Ceiling: 100 mg/m3  
Ethylene Glycol OSHA PEL - 1989(revoked) Ceiling: 50 ppmv

## EXPOSURE CONTROLS

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.

## PERSONAL PROTECTION

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation. Information on the selection of eye, skin and respiratory protection for use with this material is provided below.

## Eye Protection:

Chemical Goggles, or Safety glasses with side shields

## Skin Protection:

Use protective clothing which is chemically resistant to this material. Selection of protective clothing depends on potential exposure conditions and may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by:  
Neoprene, or Nitrile Rubber

## Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include:

For Mist: Air Purifying, R or P style NIOSH approved respirator.

For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator. Self-contained breathing apparatus for use in environments with unknown concentrations or emergency situations.

---

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance & Odor: Purple liquid. Odorless.  
Substance Chemical Family: Ethylene Glycols  
Appearance: Purple liquid.

Boiling Point: 388 °F

Flash Point: 265 °F [Cleveland Open Cup]

Freezing Point: -34 °F

Odor: Odorless.

pH: 10.2 - 11

Specific Gravity: 1.11 - 1.14

NOTE: The freezing and boiling point values reflect a 50% solution in water at atmospheric pressure.

---

SECTION 10 REACTIVITY AND STABILITY

---

Materials to Avoid:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:

Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Carbon Monoxide, Carbon Dioxide and other unidentified organic compounds may be formed upon combustion.

---

SECTION 11 TOXICOLOGICAL INFORMATION

---

Acute Toxicity

Dermal LD50 9.5 g/kg(Rabbit) OSHA: Non-Toxic Based on components(s)

Oral LDLo 0.4 g/kg(Human) OSHA: Toxic Based on components(s)

Carcinogenicity Classification

Coolant/Antifreeze

NTP: No IARC: Not Reviewed ACGIH: No OSHA: No

Developmental Toxicity

Oral exposure of pregnant rats and mice to ethylene glycol has produced birth defects in the offspring.

Kidney

Ingestion of ethylene glycol can cause bladder stones and kidney damage which can be fatal.

Liver

Prolonged and repeated ingestion of ethylene glycol has produced liver damage in rats.

---

SECTION 12 ECOLOGICAL INFORMATION

---

Environmental Impact Summary:

There is no ecological data available for this product.

---

SECTION 13 DISPOSAL CONSIDERATIONS

---

RCRA Information:

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

---

SECTION 14 TRANSPORT INFORMATION

---

US Department of Transportation Classification

This material is not regulated under 49 CFR if in a container of 119 gallon capacity or less. If shipped in a container of over 119 gallon capacity then the DOT information must be accompanied with RQ notation, or, an otherwise 'Not Regulated' product will be classified as Environmentally Hazardous (solid/liquid) N.O.S., Class 9, Packing group III unless the product qualifies for the petroleum exemption (49 CFR 171.8).

Hazardous Substance/Material RQ: Ethylene glycol / 10504.2017 lbs

International Air Transport Association

Hazard Class/Division: 9 (Miscellaneous)  
Identification Number: UN3082  
Packing Group: III  
Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S.  
Technical Name(s): Ethylene Glycol

International Maritime Organization Classification

Hazard Class/Division: 9 (Miscellaneous)  
Identification Number: UN3082  
Packing Group: III  
Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S.  
Technical Name(s): Ethylene Glycol

---

SECTION 15 REGULATORY INFORMATION

---

FEDERAL REGULATORY STATUS

OSHA Classification:

Product is hazardous according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Comprehensive Environmental Release, Compensation & Liability Act (CERCLA):

Ethylene Glycol RQ 5000 lbs Reportable Spill => 10504 lbs or 1260 gal

Potassium hydroxide RQ 1000 lbs Reportable Spill => 285714 lbs or 34271 gal

Ozone Depleting Substances (40 CFR 82 Clean Air Act):

This material does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances.

Superfund Amendment & Reauthorization Act (SARA) Title III:

There are no components in this product on the SARA 302 list.

SARA Hazard Categories (311/312):

Immediate Health: YES    Delayed Health: NO    Fire: NO    Pressure: NO  
Reactivity: NO

SARA Toxic Release Inventory (TRI) (313):

Ethylene Glycol

Toxic Substances Control Act (TSCA) Status:

All component(s) of this material is(are) listed on the EPA/TSCA Inventory of Chemical Substances.

This product may be subject to export notification under TSCA Section 12(b);  
Contains: Nitrous acid, sodium salt

Other Chemical Inventories:

Component(s) of this material is (are) listed on the Canadian DSL,

State Regulation

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

New Jersey Right-To-Know Chemical List:

Ethylene Glycol (0878) 45 - 54.99 %weight Special Hazard

Pennsylvania Right-To-Know Chemical List:

1,2-Ethanediol (107-21-1) 45 - 54.99 %weight Environmental Hazard

---

SECTION 16            OTHER INFORMATION

---

Revision#: 1

Revision Date: 10/27/2003

Revisions since last change (discussion): This Material Safety Data Sheet (MSDS) has been newly reviewed to fully comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-1998). We encourage you to take the opportunity to read the MSDS and review the information contained therein.

---

SECTION 17            LABEL INFORMATION

---

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR

OTHER RELATED REGULATORY REQUIREMENTS.

PRODUCT CODE(S): 94069

SHELL™ DIESEL READY Coolant/AF Prediluted 50/50

WARNING!

MAY BE FATAL IF INHALED. TOXIC AND HARMFUL IF SWALLOWED. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

MAY CAUSE DAMAGE TO: Kidney, Liver

Refer to Section 11, Toxicological Information, for specific information on the following effects:  
Developmental Toxicity

Precautionary Measures:

Avoid breathing of vapors, fumes, or mist. Do not take internally. Use only with adequate ventilation. Keep container closed when not in use. Avoid prolonged and repeated contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID

Inhalation: DO NOT attempt to rescue victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.  
Skin Contact: Flush exposed area with water and follow by washing with soap if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.  
Eye Contact: Flush eyes with plenty of water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision or swelling occur, transport to nearest medical facility for additional treatment.  
Ingestion: DO NOT take internally. DO NOT INDUCE VOMITING. If victim is alert, rinse mouth and drink 1/2 to 1 glass of water to help dilute the material and call a doctor or poison control center. DO NOT GIVE LIQUIDS TO A DROWSY, CONVULSING OR UNCONSCIOUS PERSON. Keep the victim calm. Transport to the nearest medical facility for additional treatment.

FIRE

In case of fire, Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

SPILL OR LEAK

Dike and contain spill.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

CONTAINS: Ethylene Glycol, 107-21-1; Deionized water, 7732-18-5; Scale and corrosion additives, Mixture

NFPA Rating (Health, Fire, Reactivity): 2, 1, 0

TRANSPORTATION

US Department of Transportation Classification

This material is not regulated under 49 CFR if in a container of 119 gallon

capacity or less. If shipped in a container of over 119 gallon capacity then the DOT information must be accompanied with RQ notation, or, an otherwise 'Not Regulated' product will be classified as Environmentally Hazardous (solid/liquid) N.O.S., Class 9, Packing group III unless the product qualifies for the petroleum exemption (49 CFR 171.8).

Hazardous Substance/Material RQ: Ethylene glycol / 10504.2017 lbs

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

Name and Address

SOPUS Products  
P.O. Box 4453  
Houston, TX 77210-4453

ADMINISTRATIVE INFORMATION

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX.  
77210-4453

Company Product Stewardship & Regulatory Compliance Contact: Timothy W Childs  
Phone Number: (281) 874-7708

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT : IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF SOPUS PRODUCTS AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF SOPUS PRODUCTS.

38200-11914-100R-10/27/2003