



MATERIAL SAFETY DATA SHEET
Revision Date: 09/30/2003

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: Shell™ DONAX® TC 10W
MSDS NUMBER: 60482E - 3
PRODUCT CODE(S): 53082

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX. 77210-4453

TELEPHONE NUMBERS

Spill Information: (877) 242-7400
Health Information: (877) 504-9351
MSDS Assistance Number: (877) 276-7285

SECTION 2 PRODUCT/INGREDIENTS

CAS#	CONCENTRATION	INGREDIENTS
		Transmission / Hydraulic Fluid
Mixture	90 - 98.99 %weight	Highly refined petroleum oils
27985-91-7	1 - 2.99 %weight	Zinc dialkaryldithiophosphate
Mixture	1 - 2.99 %weight	Additives

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance & Odor: Pale amber liquid. Slight additive odor.

Health Hazards: May cause eye irritation. High-pressure injection under the skin may cause serious damage.

Physical Hazards: No known physical hazards.

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3

Extreme - 4

Inhalation:

Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.

Eye Irritation:

May be irritating to the eyes causing a burning sensation, redness, swelling and/or blurred vision.

Skin Contact:

May cause slight irritation of the skin. If irritation occurs, a temporary burning sensation and minor redness and/or swelling may result. Release of

the material during high-pressure applications may result in injection under the skin causing possible extensive tissue damage which is difficult to heal. Other adverse effects not expected from brief skin contact.

Ingestion:

Lubricating oils are generally no more than slightly toxic if swallowed.

Other Health Effects:

Material may release hydrogen sulfide (H₂S), a highly toxic and extremely flammable gas, when heated to 180 Degrees F or higher. H₂S can cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, vomiting, diarrhea, and pulmonary edema. The odor ("rotten egg") threshold is 0.02 ppm. Do not depend on sense of smell for warning; H₂S rapidly deadens the sense of smell.

Signs and Symptoms:

Irritation as noted above. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

Aggravated Medical Conditions:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

For additional health information, refer to section 11.

SECTION 4 FIRST AID MEASURES

Inhalation:

If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin:

Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye:

Flush with water. If irritation occurs, get medical attention. If redness, burning, blurred vision or swelling persist, transport to nearest medical facility for additional treatment.

Ingestion:

Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. Have victim rinse mouth out with water, then drink sips of water to remove taste from mouth. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Note to Physician:

In general, emesis induction is unnecessary in high viscosity, low volatility products such as oils and greases.

SECTION 5 FIRE FIGHTING MEASURES

Flash Point [Method]: >400 °F/>204.44 °C [Cleveland Open Cup]

Extinguishing Media:

Material will float and can be re-ignited on surface of water. Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions:

Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures:

May burn although not readily ignitable.

Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

Spill Management:

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Place in container for proper disposal.

Reporting:

CERCLA: Product is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) petroleum exclusion. Releases to air, land, or water are not reportable under CERCLA (Superfund).

CWA: This product is an oil as defined under Section 311 of EPA's Clean Water Act (CWA). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

SECTION 7 HANDLING AND STORAGE

Precautionary Measures:

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

NIOSH approved respirator.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance & Odor: Pale amber liquid. Slight additive odor.

Substance Chemical Family: Lubricants

Appearance: Pale amber liquid.

Flash Point: > 400 °F [Cleveland Open Cup]

Odor: Slight additive odor.

Pour Point: > -18 °F

Specific Gravity: 0.9013

Viscosity: > 40 cSt @ 40 °C

SECTION 10 REACTIVITY AND STABILITY

Stability:

Material is stable under normal conditions.

Conditions to Avoid:

Avoid heat and open flames.

Materials to Avoid:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:

Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Aldehydes, Carbon Monoxide, Carbon Dioxide, Hydrogen Sulfide, Ketones and other unidentified organic compounds may be formed upon combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute Toxicity

 Dermal LD50 >5.0 g/kg(Rat) OSHA: Non-Toxic Based on components(s)

 Oral LD50 >5.0 g/kg(Rat) OSHA: Non-Toxic Based on components(s)

Carcinogenicity Classification

Transmission / Hydraulic Fluid

 NTP: No IARC: Not Reviewed ACGIH: No OSHA: No

SECTION 12 ECOLOGICAL INFORMATION

Environmental Impact Summary:

There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

SECTION 13 DISPOSAL CONSIDERATIONS

RCRA Information:

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

SECTION 14 TRANSPORT INFORMATION

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

International Air Transport Association

Not regulated under IATA rules.

International Maritime Organization Classification

Not regulated under International Maritime Organization rules.

SECTION 15 REGULATORY INFORMATION

FEDERAL REGULATORY STATUS

OSHA Classification:

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Ozone Depleting Substances (40 CFR 82 Clean Air Act):

This material does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances.

Superfund Amendment & Reauthorization Act (SARA) Title III:

There are no components in this product on the SARA 302 list.

SARA Hazard Categories (311/312):

Immediate Health:NO Delayed Health:NO Fire:NO Pressure:NO
Reactivity:NO

SARA Toxic Release Inventory (TRI) (313):
Zinc Compounds

Toxic Substances Control Act (TSCA) Status:
All component(s) of this material is(are) listed on the EPA/TSCA Inventory of
Chemical Substances.

This product may be subject to export notification under TSCA Section 12(b);
Contains: 1-Propanol, 2-methyl-

Other Chemical Inventories:

Component(s) of this material is (are) listed on the Australian AICS,
Canadian DSL, Chinese Inventory, European EINECS, Korean Inventory,
Philippines PICCS,

State Regulation

New Jersey Right-To-Know Chemical List:

Zinc Dialkaryldithiophosphate (27985-91-7) 1 - 2.99 %weight

SECTION 16 OTHER INFORMATION

Revision#: 3

Revision Date: 09/30/2003

Revisions since last change (discussion): This Material Safety Data Sheet
(MSDS) has been newly reviewed to fully comply with the guidance contained in
the ANSI MSDS standard (ANSI Z400.1-1998). We encourage you to take the
opportunity to read the MSDS and review the information contained therein.

SECTION 17 LABEL INFORMATION

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF
PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD
COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL
IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND
MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR
OTHER RELATED REGULATORY REQUIREMENTS.

PRODUCT CODE(S): 53082

Shell™ DONAX® TC 10W

ATTENTION!

MAY CAUSE EYE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE OIL
ACNE OR DERMATITIS. HIGH-PRESSURE INJECTION UNDER SKIN MAY CAUSE SERIOUS
DAMAGE.

Precautionary Measures:

Avoid prolonged or repeated contact with eyes, skin and clothing. Avoid breathing of vapors, fumes, or mist. Use only with adequate ventilation. Wash thoroughly after handling.

FIRST AID

Inhalation: If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye Contact: Flush with water. If irritation occurs, get medical attention. If redness, burning, blurred vision or swelling persist, transport to nearest medical facility for additional treatment.

Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Have victim rinse mouth out with water, then drink sips of water to remove taste from mouth.

FIRE

In case of fire, Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO₂) to extinguish flames. Do not use a direct stream of water. Material will float and can be re-ignited on surface of water.

SPILL OR LEAK

Dike and contain spill.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

CONTAINS: Highly refined petroleum oils, Mixture; Zinc dialkaryldithiophosphate, 27985-91-7; Additives, Mixture

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

TRANSPORTATION

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials.

Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

Name and Address

SOPUS Products
P.O. Box 4453
Houston, TX 77210-4453

ADMINISTRATIVE INFORMATION

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX.
77210-4453

Company Product Stewardship & Regulatory Compliance Contact: Timothy W Childs
Phone Number: (281) 874-7708

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT : IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF SOPUS PRODUCTS AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF SOPUS PRODUCTS.

38246-11474-100R-11/11/2003