

# Material Safety Data Sheet

**Shell Ensis DWO 600**  
MSDS# 10324  
Version 1.0  
Effective Date 04/24/2008  
According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

---

## 1. MATERIAL AND COMPANY IDENTIFICATION

**Material Name** : **Shell Ensis DWO 600**  
**Uses** : Corrosion protective.  
**Company** : SOPUS Products  
P.O. Box 4427  
Houston, TX 77210-4427  
United States

**MSDS Request** : 877-276-7285

**Emergency Telephone Number**  
**Spill Information** : 877-242-7400  
**Health Information** : 877-504-9351

---

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

---

## 3. HAZARDS IDENTIFICATION

<b>Emergency Overview</b>	
<b>Appearance and Odour</b>	: Brown. Clear. liquid Slight hydrocarbon.
<b>Health Hazards</b>	: Harmful: may cause lung damage if swallowed.
<b>Safety Hazards</b>	: Not classified as flammable but will burn.
<b>Environmental Hazards</b>	: Not classified as dangerous for the environment.

**Health Hazards**

- Inhalation** : Slightly irritating to respiratory system.
- Skin Contact** : Repeated exposure may cause skin dryness or cracking.
- Eye Contact** : May cause slight irritation to eyes.
- Ingestion** : Harmful: may cause lung damage if swallowed.
- Other Information** : Used oil may contain harmful impurities.

**Signs and Symptoms** : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Ingestion may result in nausea, vomiting and/or diarrhoea.

**Aggravated Medical Condition** : Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this material: Skin. Respiratory system.

**Environmental Hazards** : Not classified as dangerous for the environment.

**Additional Information** : Under normal conditions of use or in a foreseeable emergency, this product meets the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# Material Safety Data Sheet

Shell Ensis DWO 600

MSDS# 10324

Version 1.0

Effective Date 04/24/2008

According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

---

## 4. FIRST AID MEASURES

- Inhalation** : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- Skin Contact** : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
- Eye Contact** : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
- Ingestion** : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101 ° F (37° C), shortness of breath, chest congestion or continued coughing or wheezing.
- Advice to Physician** : Treat symptomatically. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal. Call a doctor or poison control centre for guidance.

---

## 5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

- Flash point** : 102 °C / 216 °F
- Upper / lower Flammability or Explosion limits** : Typical 1 - 10 %(V)(based on mineral oil)
- Auto ignition temperature** : > 320 °C / 608 °F
- Specific Hazards** : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
- Suitable Extinguishing Media** : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable Extinguishing Media** : Do not use water in a jet.
- Protective Equipment for Firefighters** : Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

---

## 6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

- Protective measures** : Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

**Material Safety Data Sheet**

**Clean Up Methods** : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

**7. HANDLING AND STORAGE**

**General Precautions** : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

**Handling** : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

**Storage** : Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: 0 - 50 °C / 32 - 122 °F

**Recommended Materials** : For containers or container linings, use mild steel or high density polyethylene.

**Unsuitable Materials** : PVC.

**Additional Information** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Occupational Exposure Limits**

Material	Source	Type	ppm	mg/m3	Notation
Distillates (petroleum), hydrotreated light	ACGIH	TWA(Non-aerosol.)		200 mg/m3	as total hydrocarbon vapor
Distillates (petroleum), hydrotreated light	ACGIH	SKIN_DES(Non-aerosol.)			Can be absorbed through the skin.as total hydrocarbon vapor
Distillates (petroleum), hydrotreated light	ACGIH	TWA(Non-aerosol.)		200 mg/m3	as total hydrocarbon vapor

**Material Safety Data Sheet**

Distillates (petroleum), hydrotreated light	ACGIH	SKIN_DES(N on-aerosol.)			Can be absorbed through the skin.as total hydrocarbon vapor
	OSHA Z1	PEL	500 ppm	2,000 mg/m3	
	OSHA Z1A	TWA	400 ppm	1,600 mg/m3	
Oil mist, mineral	ACGIH	TWA(Mist.)		5 mg/m3	
Oil mist, mineral	ACGIH	STEL(Mist.)		10 mg/m3	

- Exposure Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- Personal Protective Equipment** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)].
- Hand Protection** : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- Eye Protection** : Wear safety glasses or full face shield if splashes are likely to occur.
- Protective Clothing** : Skin protection not ordinarily required beyond standard issue work clothes.
- Monitoring Methods** : Monitoring of the concentration of substances in the breathing

# Material Safety Data Sheet

Shell Ensis DWO 600

MSDS# 10324

Version 1.0

Effective Date 04/24/2008

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

**Environmental Exposure Controls** : Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Brown. Clear. liquid  
Odour : Slight hydrocarbon.  
pH : Not applicable.  
Initial Boiling Point and Boiling Range : > 280 °C / 536 °F estimated value(s)  
Flash point : 102 °C / 216 °F  
Upper / lower Flammability or Explosion limits : Typical 1 - 10 %(V) (based on mineral oil)  
Auto-ignition temperature : > 320 °C / 608 °F  
Vapour pressure : < 0.5 Pa at 20 °C / 68 °F (estimated value(s))  
Density : 0.83 g/cm<sup>3</sup>  
Water solubility : Negligible.  
n-octanol/water partition coefficient (log Pow) : > 6 (based on information on similar products)  
Kinematic viscosity : 6.0 mm<sup>2</sup>/s at 40 °C / 104 °F  
Vapour density (air=1) : > 1 (estimated value(s))  
Evaporation rate (nBuAc=1) : Data not available

---

## 10. STABILITY AND REACTIVITY

**Stability** : Stable.  
**Conditions to Avoid** : Extremes of temperature and direct sunlight.  
**Materials to Avoid** : Strong oxidising agents. DO NOT add nitrites or any nitrosating agents. May react with amines and form nitrosamines which cause cancer in animal tests.  
**Hazardous Decomposition Products** : Hazardous decomposition products are not expected to form during normal storage.

---

## 11. TOXICOLOGICAL INFORMATION

**Basis for Assessment** : Information given is based on data on the components and the toxicology of similar products.  
**Acute Oral Toxicity** : Expected to be of low toxicity: LD50 >2000 mg/kg , Rat  
Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.  
**Acute Dermal Toxicity** : Expected to be of low toxicity: LD50 >2000 mg/kg , Rabbit  
**Acute Inhalation Toxicity** : Not expected to be a hazard.  
**Skin Irritation** : Expected to be slightly irritating. Repeated exposure may cause skin dryness or cracking.  
**Eye Irritation** : Expected to be slightly irritating.  
**Respiratory Irritation** : Inhalation of vapours or mists may cause irritation.  
**Sensitisation** : Not expected to be a skin sensitiser.

**Material Safety Data Sheet**

- Repeated Dose Toxicity** : Not expected to be a hazard.
- Mutagenicity** : Not considered a mutagenic hazard.
- Carcinogenicity** : Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
- Reproductive and Developmental Toxicity** : Not expected to be a hazard.
- Additional Information** : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. Properly manage used fluids. Used metalworking fluids may accumulate harmful bacteria. Breathing mists generated during use may cause hypersensitivity pneumonitis or aggravate existing asthma symptoms. DO NOT add nitrites or any nitrosating agents. May react with amines and form nitrosamines which cause cancer in animal tests.

---

**12. ECOLOGICAL INFORMATION**

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

- Acute Toxicity** : Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.
- Mobility** : Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
- Persistence/degradability** : Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
- Bioaccumulation** : Contains components with the potential to bioaccumulate.
- Other Adverse Effects** : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

---

**13. DISPOSAL CONSIDERATIONS**

- Material Disposal** : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper

# Material Safety Data Sheet

Shell Ensis DWO 600

MSDS# 10324

Version 1.0

Effective Date 04/24/2008

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

- waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
- Container Disposal** : Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
- Local Legislation** : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

## 14. TRANSPORT INFORMATION

### US Department of Transportation Classification (49CFR)

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

### IMDG

This material is not classified as dangerous under IMDG regulations.

### IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

---

## 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

### Federal Regulatory Status

#### Notification Status

TSCA	All components in compliance.
DSL	All components in compliance.
EINECS	All components in compliance.

### SARA Hazard Categories (311/312)

Immediate (Acute) Health Hazard.

### State Regulatory Status

#### California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

# Material Safety Data Sheet

Shell Ensis DWO 600  
MSDS# 10324  
Version 1.0  
Effective Date 04/24/2008  
According to OSHA Hazard Communication Standard, 29 CFR  
1910.1200

## New Jersey Right-To-Know Chemical List

Distillates (petroleum), hydrotreated light (64742-47-8) Listed.  
Listed.

## Pennsylvania Right-To-Know Chemical List

Distillates (petroleum), hydrotreated light (64742-47-8) Listed.  
(64742-52-5) Listed.

---

## 16. OTHER INFORMATION

- NFPA Rating (Health, Fire, Reactivity)** : 1, 1, 0  
**MSDS Version Number** : 1.0  
**MSDS Effective Date** : 04/24/2008  
**MSDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.  
**MSDS Regulation** : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
**MSDS Distribution** : The information in this document should be made available to all who may handle the product.  
**Disclaimer** : The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.