

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)
Product name	MAXLIFE® SAE 20W-50 HIGH MILEAGE MOTOR OIL	
Product code	VV161	
Product Use Description	No data	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin contact, Eye Contact, Ingestion

Eye contact

Unlikely to cause eye irritation or injury.

Skin contact

Unlikely to cause skin irritation or injury. Prolonged or repeated contact may dry and crack the skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing this material is not likely to be harmful.

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=40-<50%
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	>=20-<30%

4. FIRST AID MEASURES

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

First aid is not normally required. If symptoms develop, seek medical attention.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water mist, Carbon dioxide (CO₂), Dry chemical

Hazardous combustion products

carbon dioxide and carbon monoxide, nitrogen oxides (NO_x), sulfur oxides, Oxides of phosphorus, various hydrocarbons

Precautions for fire-fighting

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Environmental precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

Storage

Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

AROMATIC HYDROCARBON

OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,000 mg/m3	
OSHA Z1A	time weighted average	400 ppm	
OSHA Z1A	time weighted average	1,600 mg/m3	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	400 ppm	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	1,600 mg/m3	
ACGIH	time weighted average	5 mg/m3	Mist.
ACGIH	Short term exposure limit	10 mg/m3	Mist.
ACGIH NIC	time weighted average	0.2 mg/m3	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161**Skin and body protection**

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product.

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	No data
Odour	No data
Boiling point/boiling range	315.56 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas
pH	No data
Flash point	(>) 199.00 °C Cleveland open cup
Evaporation rate	No data
Lower explosion limit/Upper explosion limit	0.9 %(V) / 7 %(V)
Vapour pressure	0.133 hPa @ 20 °C Calculated Vapor Pressure
Vapour density	No data
Density	0.8850 g/cm ³ @ 60.01 °F / 15.56 °C
Solubility	No data
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY**Stability**

Stable.

Conditions to avoid

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

None known.

Incompatible products

strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50 Rat: > 15 g/kg
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : LD 50 Rat: > 15 g/kg

Acute inhalation toxicity

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Acute dermal toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50 Rabbit: > 5 g/kg
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : LD 50 Rabbit: > 5 g/kg

12. ECOLOGICAL INFORMATION

Biodegradability

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Bioaccumulation

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

Ecotoxicity effects

Toxicity to fish

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Toxicity to daphnia and other aquatic invertebrates.

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Toxicity to algae

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Toxicity to bacteria

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Biochemical Oxygen Demand (BOD)

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Chemical Oxygen Demand (COD)

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

Additional ecological information

HEAVY PARAFFINIC DISTILLATE : no data available
Distillates (Petroleum), Hydrotreated Heavy Paraffinic : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

No SARA Hazards

New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7
SEVERELY TREATED BASE OIL
AROMATIC HYDROCARBON

Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7
SEVERELY TREATED BASE OIL
AROMATIC HYDROCARBON

Notification status

US. Toxic Substances Control Act y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). q (quantity restricted)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)
Australia. Industrial Chemical (Notification and Assessment) Act n (Negative listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand n (Negative listing)
Japan. Kashin-Hou Law List n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List n (Negative listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act n (Negative listing)
China. Inventory of Existing Chemical Substances q (quantity restricted)

ASHLAND
SAFETY DATA SHEET

Page: 11
Revision Date: 02/19/2010
Print Date: 3/31/2010
MSDS Number: R0355889
Version: 2.0

MAXLIFE® SAE 20W-50 HIGH MILEAGE
MOTOR OIL
VV161

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).