

The Valvoline Company

Date Prepared: 01/14/02

MSDS No: 505.0191783-004.011I

PYROIL HONDA POWER STEERING FLD 12/12 OZ

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL HONDA POWER STEERING FLD 12/12 OZ

General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

Company

The Valvoline Company
P.O. Box 14000
Lexington, KY 40512

Telephone Numbers

Emergency: 1-800-274-5263
Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
PETROLEUM DISTILLATE	64742-55-8	71.0- 81.0
HYDRAULIC FLUID ADDITIVE		3.0- 13.0
ZINC ALKYL DITHIOPHOSPHATE		0.0- 6.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Unlikely to cause eye irritation or injury.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), pain in the abdomen.

Target Organ Effects

No data

Developmental Information

No data

Cancer Information

No data

Other Health Effects
No data

Primary Route(s) of Entry
Inhalation, Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Do not induce vomiting. Give one glass of milk or water, and get medical attention immediately. If possible, do not leave victim unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

> 320.0 F (160.0 C) COC

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 1, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up is completed. Stop spill at source. Dike to prevent spreading. Pump to salvage tank.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use. However, if misting or splashing conditions exist, then safety glasses or chemical splash goggles are advised.

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product. Wear normal work clothing covering arms and legs.

Respiratory Protections

Not required under normal conditions of use. However, if oil mists are generated above recommended PEL/TLV of 5 mg/m³, then a NIOSH/MSHA approved respirator is advised in absence of proper environmental control. (See your industrial hygienist.)

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines

Component

PETROLEUM DISTILLATE (64742-55-8)
No exposure limits established

HYDRAULIC FLUID ADDITIVE
No exposure limits established

ZINC ALKYL DITHIOPHOSPHATE
No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point
No data

Vapor Pressure
(for component) < .040 mmHg @ 68.00 F

Specific Vapor Density
> 1.000 @ AIR=1

Specific Gravity
.887 @ 77.00 F

Liquid Density
7.380 lbs/gal @ 77.00 F
.887 kg/l @ 25.00 C

Percent Volatiles (Including Water)
No data

Evaporation Rate
SLOWER THAN ETHYL ETHER

Appearance
No data

State
LIQUID

Physical Form
HOMOGENEOUS SOLUTION

Color
ASTM COLOR 5.0

Odor
No data

pH
No data

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4
None

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate() Delayed() Fire() Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65
None

International Regulations
Inventory Status
Not determined

State and Local Regulations
California Proposition 65
None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page