

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	SYNPOWER® SAE 5W-20 SYNTHETIC MOTOR OIL
Product code	VV92755
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid,, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Routes of exposure

Inhalation, Skin contact, Eye Contact, Ingestion

Eye contact

Unlikely to cause eye irritation or injury.

Skin contact

Unlikely to cause skin irritation or injury. Prolonged or repeated contact may dry and crack the skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

material is not likely to be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF	64742-54-7	>=80-<90%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

First aid is not normally required. If symptoms develop, seek medical attention.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam, Water spray, Carbon dioxide (CO₂), Dry chemical

Hazardous combustion products

carbon dioxide and carbon monoxide, various hydrocarbons, oxides of sulfur, nitrogen and phosphorus

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

Flammability Class for Flammable Liquids
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for cleaning up

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

<3 % DMSO DISTILLATES

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

**(PETROLEUM), SOLVENT-
DEWAXED HEAVY PA**

OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,000 mg/m ³	
OSHA Z1A	time weighted average	400 ppm	
OSHA Z1A	time weighted average	1,600 mg/m ³	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	400 ppm	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	1,600 mg/m ³	
ACGIH	time weighted average	5 mg/m ³	Mist.
ACGIH	Short term exposure limit	10 mg/m ³	Mist.
ACGIH NIC	time weighted average	0.2 mg/m ³	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product. Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	amber
Odour	mild
Boiling point/boiling range	218.00 °C / 424 °F@ 760.00 mmHg
pH	No data
Flash point	(>)390 °F / 199 °C, Closed Cup
Evaporation rate	< 1 (Ethyl Ether)
Explosion limits	1 %(V) 6 %(V)
Vapour pressure	0.13 hPa @ 68 °F / 20 °C
Vapour density	(>) 1 (AIR=1)
Density	0.8530 g/cm ³ @ 60.01 °F / 15.56 °C 7.08 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

No hazards to be specially mentioned.

Conditions to avoid

None known.

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus

Hazardous reactions

Hazardous polymerisation does not occur.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF	LD 50 Rat: > 15 g/kg
--	----------------------

Acute inhalation toxicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF	no data available
--	-------------------

Acute dermal toxicity

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAF	LD 50 Rabbit: > 5 g/kg
--	------------------------

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

SYNPOWER® SAE 5W-20
SYNTHETIC MOTOR OIL VV92755

14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

Reportable quantity - Components

DISTILLATES (PETROLEUM), 64742-54-7 none
HYDROTREATED HEAVY PARAF

	Health	Flammability	Reactivity	Other
HMIS	1	1	0	
NFPA	1	1	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).