

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	Zerex® G-05® RTU ANTIFREEZE COOLANT
Product code	ZXG05RU1
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, light yellow

WARNING! MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION.

Potential Health Effects

Routes of exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Although rare, skin contact with ethylene glycol may cause allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. Liver, kidney and brain damage in humans has resulted from swallowing lethal or near-lethal amounts of ethylene glycol.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., lung (for example, asthma-like conditions), liver, kidney, Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, involuntary eye movement, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), lung edema (fluid buildup in the lung tissue), acute kidney failure (sudden slowing or stopping of urine production), liver damage, convulsions, coma

Target Organs

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:., reproductive effects, kidney damage, liver damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans:., kidney damage, liver damage

Carcinogenicity

This material is not expected to cause cancer in humans since it did not cause cancer in laboratory animals. This material is not listed as a carcinogen by the

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

Ethylene glycol has caused birth defects in animal studies at high oral doses. However, it did not cause harm to the pregnant animal or to the fetus when applied to the skin of the pregnant animal.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ETHYLENE GLYCOL	107-21-1	>=40-<50%
ORGANIC SALT	NJTS# 254504001-5054	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

Hazards: Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Treatment: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical, Agents approved for class B hazards or water fog.

Hazardous combustion products

alcohols, aldehydes, carbon dioxide and carbon monoxide, ethers, toxic fumes, sodium oxides, various hydrocarbons

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Organic dusts at sufficient concentration can form explosive mixtures in air. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

spreading burning liquid with water used for cooling purposes. No special precautions necessary when fighting fires involving this product.

Flammability Class for Flammable Liquids
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

No data

Environmental precautions

No data

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill. Collect material with vacuum cleaner. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Do not flush into sewers. Material should be placed in a container for recovery or transfer to a disposal facility.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances. Store in a cool, dry, ventilated area. Keep containers closed when not in use. Do not store near extreme heat, open flame, or sources of ignition.

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

ETHYLENE GLYCOL

107-21-1

ACGIH	Ceiling Limit Value:	100 mg/m ³	Aerosol.
-------	----------------------	-----------------------	----------

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves such as:

Neoprene
Nitrile rubber
polyvinyl chloride
Polyethylene

Respiratory protection

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	light yellow
Odour	No data
Boiling point/boilingrange	225.00 °F / 225 °F @ 760.00 mmHg
pH	(Average) 8.0
Flash point	(>)250.0 °F / 121.1 °C, Cleveland open cup
Evaporation rate	No data
Explosion limits	1.7 %(V) 15.3 %(V)
Vapour pressure	1.80 mmHg @ 68.00 °F / 20.00 °C
Vapour density	(>) 1.000 (AIR=1)
Density	(Average) 1.0827 g/cm ³ @ 60.01 °F / 15.56 °C 8.99 lb/gal
Solubility	No data
Partition coefficient: n-octanol/water	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to avoid

Incompatible products

Avoid contact with:, Alkaline earth metals, Alkali metals, strong acids, strong alkalis, strong oxidizing agents, sulphur compounds, iron salts, strong mineral acids

Hazardous decomposition products

May form:, carbon dioxide and carbon monoxide

Hazardous reactions

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

ETHYLENE GLYCOL	LD 50 Rat: 6,140 mg/kg LD 50 Mouse: 14,600 mg/kg
ORGANIC SALT	LD 50 Rat: 4,070 mg/kg

Acute inhalation toxicity

ETHYLENE GLYCOL	no data available
ORGANIC SALT	no data available

Acute dermal toxicity

ETHYLENE GLYCOL	LD 50 Rabbit: 10,611 mg/kg
ORGANIC SALT	no data available

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Destroy by liquid incineration in accordance with applicable regulations. For assistance with your waste management needs - including disposal, recycling and waste

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated above) may not reflect package size, quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

ETHYLENE GLYCOL	107-21-1	42.4941%
-----------------	----------	----------

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302)	11766 lbs
--	-----------

Reportable quantity - Components

ETHYLENE GLYCOL	107-21-1	5000 lbs
ORGANIC SALT	NJTS# 254504001-5054	none

	Health	Flammability	Reactivity	Other
HMIS	1*	1	0	
NFPA	1	1	0	

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their

ASHLAND
SAFETY DATA SHEET

Page: 10
Revision Date: 03/04/2008
Print Date: 6/10/2008
MSDS Number: R0321370
Version: 1.7

Zerex® G-05® RTU ANTIFREEZE
COOLANT
ZXG05RU1

circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).